BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images, please do not report the images to the Image Problem Mailbox.

Fig. 1


143
CLOCK
131
102
Pulsed source
130
140
120
142
101
Data source
One or more hybrids
One or more sets of balanced detectors
A/D
Processor
110
141

Fig. 2


130
131
D
Pulser
102
Hybrid
Sampling laser
202
120
140
Filter
Es
213
BDA
A/D
Processor
PC
Ed
211
210
214
BDB
DATA
142
Source under test
212
V
130
201
101
110

Fig. 3


Data rate
101
Data
source
102
Pulse
source
142
Data
output
sample rate

Fig. 5


(A)
(B)
(C)
Amplitude (a.u.)
0 5 10 15 20
Sampling event
0 5 10 15 20
Sampling event
0 5 10 15 20
Sampling event

140

Fig. 4

A. Numerically scales the two quadratures interference samples S_A and S_B over a large collection of samples by imposing that $\langle S_A \rangle = \langle S_B \rangle = 0$ and $\langle S_A^2 \rangle = \langle S_B^2 \rangle$, where the brackets represent the average value calculated over a large number of samples. This can be achieved by:

- a. Calculating $\langle S_A \rangle$, then calculating $S_A' = S_A - \langle S_A \rangle$ and using it for all subsequent operations.
- b. Calculating $\langle S_B \rangle$, then calculating $S_B' = S_B - \langle S_B \rangle$ and using it for all subsequent operations.
- c. Calculating $\sigma_A'^2 = \langle S_A'^2 \rangle$, then calculating $\sigma_B'^2 = \langle S_B'^2 \rangle$, then defining S_A'' and S_B'' such as $S_A'' = S_A''/\sigma_A'$ and $S_B'' = S_B''/\sigma_B'$. Note that other scalings techniques can be performed (what matters in the end is that the standard variation calculated on the two quadratures are identical).

B. Calculates the quantity $2 \langle S_A'' \cdot S_B'' \rangle / (\langle S_A''^2 \rangle + \langle S_B''^2 \rangle)$, which is equal to the cosine of the relative phase between the two quadratures [i.e., $\cos(\varphi_B - \varphi_A)$]. As the relative phase should be equal to either $+\pi/2$ or $-\pi/2$ for optimal operation, its cosine should be equal to 0.

C. Adjusts the relative phase between the two quadratures so that the calculated $2 \langle S_A'' \cdot S_B'' \rangle / (\langle S_A''^2 \rangle + \langle S_B''^2 \rangle)$ is close to zero, within experimental uncertainty. With the hybrid, this operation is performed by the processor 140 adjusting, via phase adjust control signal 141, the voltage applied to the phase-shifter (212 of Fig. 2).

D. The processor then generates a demodulated sample data pulse signal 142 equal to the sum $S_A''^2 + S_B''^2$.

Fig. 6


E_D 101
E_S 102
601
602
603
604
611
612
613
614
212
600
S_A
S_B
120
121
BDA
BDB

Fig. 7


E_D
E_S
701
702
703
704
710
711
712
713
212
X
Y
BDA
BDB
BDC
BDD
S_A
S_B
S_C
S_D

Fig. 8


810
212
BDA
S_A
E_S
802
X
BDB
S_B
E_D
801
X
X
803
Y
BDC
S_C
Y
212
BDD
S_D
820

Fig. 9


212
911
X
BDA
S_A
902
Y
912
X
E_D
901
BDB
S_B
Y
913
X
E_S
BDC
S_C
903
904
Y
914
X
BDD
S_D
Y
600

Fig. 10


E_D
1001
Delay box 1
E_S
Delay box 2
1002
212
BDA
S_A
BDB
S_B
1010

Fig. 11


1151 Clock
1131
1102
Pulsed source
1103
1140
1120
1101
One or more hybrids
One or more sets of balanced detectors
A/D
Processor
1142
1110
1141